

# I AANBOUWVERDICHTER

		I HD250	I HD500	I HD800	I HD1200	I HD1500	I HD2000
<b>A</b>	<b>Hoogte (zonder adapterplaat)</b>	560 mm	645 mm	785 mm	875 mm	940 mm	990 mm
<b>B</b>	<b>Breedte</b>	380 mm	510 mm	660 mm	770 mm	900 mm	1100 mm
<b>C</b>	<b>Lengte</b>	740 mm	864 mm	1100 mm	1320 mm	1460 mm	1550 mm
	<b>Gewicht (incl. vervangframe)</b>	240 kg	370 kg	780 kg	1.170 kg	1.470 kg	1.800 kg
	<b>Aanbev. baggergrootte</b>	1,5 - 6 t	5 - 10 t	7 - 20 t	15 - 30 t	20 - 60 t	20 - 60 t
	<b>Frequentiebereik</b>	28 - 60 Hz	28 - 60 Hz	28 - 60 Hz	28 - 60 Hz	28 - 60 Hz	28 - 50 Hz
	<b>Dynamische slagkracht</b>	580 - 2.600 kg	1.000 - 4.400 kg	2.000 - 8.300 kg	3.500 - 15.000 kg	5.000 - 21.000 kg	10.000 - 30.000 kg
	<b>Max. toelaatbare werkdruk</b>	160	210	210	210	210	210
	<b>Aanbevolen min. debiet</b>	30	60	90	150	210	210

